



RF/GF 519

- Wheel position: Drive
- For highway and regional operation
- Tough blocks provide strong off-road performance
- Special self-cleaning design
- Deep grooves for high mileage

Product Number	Tire Size	PR	Pattern	Weight (lbs/kg)	Rim Size (in)	Tread Depth (32nds/mm)	Load Index S/D & Speed S	Section Width (in/mm)	Overall Diameter (in/mm)	Max. Air Single-Dual (psi/kpa)	Load Capacity Single-Dual (lbs/kg's)	Qty/40'HC	Price
63972	11R22.5	14	RF/GF 519	124/56.3	8.25	26/21	144/142 & K	11/279	42/1065	105/720-105/720	6173/2800-5842/2650	275 pcs	
63975	11R22.5	16	RF/GF 519	125/57.3	8.25	26/21	146/143 & K	11/279	42/1065	120/830-120/830	6614/3000-6008/2725	275 pcs	
63977	11R24.5	14	RF/GF 519	133/60.2	8.25	26/21	146/143 & K	11/279	43.8/1112	105/720-105/720	6614/3000-6008/2725	265 pcs	
63980	11R24.5	16	RF/GF 519	134/61.0	8.25	26/21	149/146 & K	11/279	43.8/1112	120/830-120/830	7165/3250-6614/3000	265 pcs	
63913	12R22.5	18	RF/GF 519	148/67.0	9.00	19.5/15.5	152/149 & L	11.8/300	42.7/1085	135/930-135/930	4826/3550-7165/3250	240 pcs	
63984	285/75R24.5	14	RF/GF 519	129/59.1	8.25	26/21	144/141 & K	11.1/283	41.6/1056	110/760-110/760	6173/2800-5677/2575	250 pcs	
63981	295/75R22.5	14	RF/GF 519	120/54.4	9.00	26/21	144/141 & K	11.7/298	40.2/1020	110/760-110/760	6173/2800-5677/2575	272 pcs	