



RF/GF 766

- Wheel position: Steer Axle or Regional or Trailer
- For highway operation
- Anti side slip
- Low rolling resistance
- Excellent resistance to heat build up

Product Number	Tire Size	PR	Pattern	Weight (lbs/kg)	Rim Size (in)	Tread Depth (32nds/mm)	Load Index S/D & Speed S	Section Width (in/mm)	Overall Diameter (in/mm)	Max. Air Single-Dual (psi/kpa)	Load Capacity Single-Dual (lbs/kg's)	Qty/40'HC	Price
63916	11R22.5	14	RF/GF 766	117/53.0	8.25	18.5/15	144/142 & M	11/279	41.5/1054	105/720-105/720	6173/2800-5842/2650	275	
63917	11R22.5	16	RF/GF 766	118/53.5	8.25	18.5/15	146/143 & M	11/279	41.5/1054	120/830-120/830	6614/3000-6008/2725	275	
63976	11R24.5	14	RF/GF 766	150/68.0	8.25	18.5/15	146/143 & M	11/279	43.5/1104	105/720-105/720	6614/3000-6008/2725	265	
63979	11R24.5	16	RF/GF 766	121/54.8	8.25	18.5/15	149/146 & M	11/279	43.5/1104	120/830-120/830	7165/3250-6614/3000	265	
63912	12R22.5	18	RF/GF 766	140/63.5	9.00	19.5/15.5	152/149 & M	11.8/300	42.7/1085	135/930-135/930	7826/3550-7165/3250	240	
63995	295/75R22.5	14	RF/GF 766	118/53.5	9.00	19.5/15.5	144/141 & M	11.7/298	39.9/1014	110/760-110/760	6173/2800-5677/2575	272	
63908	295/80R22.5	16	RF/GF 766	136/61.6	9.00	19.5/15.5	150/147 & M	11.7/298	41.1/1044	120/830-120/830	7385/3350-6779/3075	250	
63910	295/80R22.5	18	RF/GF 766	139/63.0	9.00	19.5/15.5	152/149 & M	11.7/298	41.1/1044	130/900-130/900	7826/3550-7165/3250	250	