



## ELECTRA IRONMAN LT66/PM66

Peak Performance for On and Off Road Versatility

Superior Tread Grip on All Terrains

### ELECTRA IRONMAN LT66

Tire Size	LI/SS	Sidewall	UTQG	Std. Rim	Section Width mm	Overall Diameter mm	Load Capacity in KG	Tread Depth in /32nds inch	Weight in KG	Qty/40 ft H/C
P215/75R15	100S	RWL	400AB	6.0	216	703	792	11.5	12.3	952
P235/75R15XL	108S	RWL	400AB	6.5	236	733	992	13.0	14.8	800
P265/75R15	112S	RWL	400AB	7.0	267	779	1122	12.0	16.7	600
P245/75R16	111S	RWL	400AB	7.0	249	774	1032	12.0	15.4	645
P265/75R16	116S	RWL	400AB	7.0	267	804	1182	12.0	18	558
P245/70R16	107S	RWL	400AB	7.0	249	750	952	12.5	15.6	657
P265/70R16	112S	RWL	400AB	8.0	272	778	1092	12.5	16.8	600
P275/70R16	114T	RWL	400AB	8.0	279	792	1182	13.0	18.3	465
LT225/75R16	115/112S	RWL	400AB	6.5	241	744	1218	16.5	20.1	732
LT235/75R15	104/101S	RWL	400AB	6.5	246	734	902	16.5	17	752
LT245/75R16	120/116S	RWL	400AB	7.0	262	774	1383	17.0	22.5	645
LT265/75R16	112/109S	RWL	400AB	7.5	287	804	1123	17.0	20.7	560
LT265/75R16	123/120S	RWL	400AB	7.0	267	804	1552	17.0	23.4	560
LT215/85R16	115/112S	RWL	400AB	6.0	246	772	1218	16.0	17.3	750
LT235/85R16	120/116S	RWL	400AB	6.5	267	806	1383	17.0	22.9	622
30X9.50R15	104S	RWL	400AB	7.5	257	750	902	15.0	17.5	675
31X10.50R15	109S	RWL	400AB	8.5	290	780	1032	16.0	20.5	540
185/R14C	102/100	RWL	400AB	5.5	188	674	1700	10.0	25	1332

### ELECTRA IRONMAN PM66

Tire Size	LI/SS	Sidewall	UTQG	Std. Rim	Section Width mm	Overall Diameter mm	Load Capacity in KG	Tread Depth in /32nds inch	Weight in KG	Qty/40 ft H/C
P235/75R15	108Q	RWL	400AB	6.5	235	733	992	12.9	14.2	800
LT235/75R15	104/101Q	RWL	400AB	6.5	235	733	902	16.5	16.5	752
LT245/75R16	120/116N	RWL	400AB	7.0	248	774	1383	17.0	21.5	645
31X10.50R15LT	109Q	RWL	400AB	8.5	274	780	1023	15.9	18.6	540
LT235/85R16	120/116N	RWL	400AB	6.5	235	806	1383	16.5	22.1	622