

HERCULES TIRES
RIDE ON OUR STRENGTH.



Terra Trac HT

M + S Rated


All Season Tread Design

Smooth & Quiet Ride for Highway Driving

Popular Fitment Sizes for All Light Truck & SUV Applications

UTQG 400 A B

Tire Size	LI/SS	Sidewall	UTQG	Std. Rim	Section Width mm	Overall Diameter mm	Load Capacity in KG	Tread Depth in /32nds inch	Weight in KG	Qty/40 ft H/C
LT225/75/R16	110/107N	BLK		6.0	215.9	744.2	1061	14.0	15.9	732
LT235/85/R16	120/116N	BLK		6.5	236.2	800.1	1383	14.0	18.2	622
LT245/75/R16	120/116N	BLK		7.0	238.8	772.2	1383	14.0	17.7	645
LT235/75/R15	104/101Q	OWL		6.5	226.1	729.0	902	14.0	14.1	752
31X10.50R15LT	109Q	OWL		8.5	266.7	762.0	1032	14.0	17.3	540
215/75R15	100S	OWL	400A B	6.0	218.4	698.0	802	11.0	11.4	952
235/75R15	105S	OWL	400A B	6.5	236.2	729.0	927	11.0	12.7	800
235/70R16	106S	OWL	400A B	7.0	238.8	729.7	952	11.0	14.1	860
245/70R16	107S	OWL	400A B	7.0	250.2	746.3	977	11.0	14.5	657
245/75R16	111S	OWL	400A B	7.0	243.8	767.1	1092	11.0	15.0	645
255/70R16	111S	OWL	400A B	7.5	261.6	744.2	1092	11.0	15.5	650
265/70R16	112S	OWL	400A B	8.0	274.3	767.1	1122	11.0	15.9	600
265/75R16	116S	OWL	400A B	7.5	269.2	795.5	1253	11.0	16.8	558



HERCULES TIRE
INTERNATIONAL

41 Ardelt Place
Kitchener, Ontario N2C 2C8

www.herculestire.com