



COMMERCIAL

Unique Steel-Belted Construction Protects Tire from Punctures, Impact Damage & Irregular Wear

Lateral Siped Tread Design Provides Excellent Water Dispersion & Braking

Wide-Arc Tread Increases Stability

COMMERCIAL

Tire Size	LI/SS	Sidewall		Std. Rim	Section Width mm	Overall Diameter mm	Load Capacity in KG	Tread Depth in /32nds inch	Weight in KG	Qty/40 ft H/C
145R12C	8PR 86/84P	BW		4.5	145	544	531/501	10	15.1	2,000
155R12C	8PR 88/86P	BW		4.5	160	556	561/531	10	16.0	1,900
155R13C	8PR 90/88P	BW		4.5	157	579	601/561	10	20.5	1,700
165R13C	8PR 94/92P	BW		4.5	170	599	671/631	12	20.0	1,500
175R14C	8PR 99/98Q	BW		5.0	180	640	777/751	10	23.8	1,250
185R14C	8PR 102/100P	BW		5.5	196	650	852/802	12	27.5	1,100
195R14C	8PR 106/104P	BW		5.5	206	668	952/902	12	28.4	1,000
215R14C	8PR 112/110Q	BW		6.0	224	701	1122/1062	12	31.5	900
195/70R15C	8PR 104/102R	BW		5.5	201	650	1800/1700	12	26.6	1,000
225/70R15C	8PR 112/110R	BW		6.5	231	709	2240/2120	13	29.7	800



41 Ardelt Place
 Kitchener, Ontario, CANADA N2C 2C8
www.herculestire.com