



TYPE Z

Ultra High Performance Uni-directional Tread Design

Maximum Dry Grip & Handling for High Performance Cars

Exceptional Anti-Hydroplaning Performance

Increased Traction & Control on Corners

Responsive Handling & Ride Comfort

TYPE - Z

Tire Size	LI/SS	Sidewall	UTQG	Std. Rim	Section Width mm	Overall Diameter mm	Load Capacity in KG	Tread Depth in /32nds inch	Weight in KG	Qty/40 ft H/C
195/50R15	82V	BW	280AA	6.0	201	577	475	10.0	10.0	1367
205/55R16	91V	BW	280AA	6.5	214	632	615	10.5	10.5	1111
215/55ZR16 RF	97W	BW	280AA	7.0	226	642	730	10.5	10.5	960
205/40ZR17 XL	84W	BW	280AA	7.5	212	596	500	10.0	10.0	1216
215/40ZR17 XL	87W	BW	280AA	7.0	213	626	545	10.0	10.9	1095
215/45ZR17 RF	91W	BW	280AA	7.0	213	626	545	10.0	11.4	1060
225/45ZR17 XL	94W	BW	280AA	7.5	225	634	670	10.0	11.4	920
235/45ZR17 RF	97W	BW	280AA	8.0	236	644	730	10.3	11.6	870
245/45R17	95W	BW	280AA	8.0	243	652	690	10.0	11.7	840
225/40ZR18 XL	92W	BW	280AA	8.0	230	637	630	10.0	11.4	930
235/40ZR18 XL	95W	BW	280AA	8.5	241	645	690	10.0	11.8	880
245/40ZR18 XL	97W	BW	280AA	8.5	248	653	730	10.0	12.3	824
255/45R18 RF	103W	BW	280AA	8.5	255	687	875	10.0	12.5	810
235/35ZR19 XL	91W	BW	280AA	8.5	241	547	615	10.0	11.8	850
245/35ZR19 XL	93W	BW	280AA	8.5	247	655	650	10.0	12.0	830