



# M600

**All Season Performance**

**Designed & Built for a Smooth & Comfortable Ride**

**Resists Hydroplaning**

**Heavily Siped Shoulder for the Most Rugged Conditions**

**Touring Design**

M600										
Tire Size	LI/SS	Sidewall	UTQG	Std. Rim	Section Width mm	Overall Diameter mm	Load Capacity in KG	Tread Depth in /32nds inch	Weight in KG	Qty/40 ft H/C
P155/80R13	79T	WW	480A	4.5	155	574	438	10.0	6.2	1950
P165/80R13	83T	WW	480A	4.5	161	589	488	10.0	6.6	1800
P175/80R13	86T	WW	480A	5.0	177	607	531	10.0	9.1	1600
P185/75R14	89T	WW	560A	5.0	178	631	581	10.5	7.6	1537
P195/75R14	92T	WW	560A	5.5	194	463	631	10.6	9.2	1370
P205/75R14	95T	WW	560A	5.5	199	661	691	10.7	9.4	1250
P215/75R14	98T	WW	560A	6.0	207	674	751	10.7	10.7	1150
P205/75R15	97T	WW	560A	5.5	194	685	731	11.3	10.5	1150
P215/75R15	100T	WW	560A	6.0	208	699	802	10.7	11.0	1000
P225/75R15	102T	WW	560A	6.0	215	715	852	10.7	11.9	950
P235/75R15	105T	WW	560A	6.5	225	731	927	11.0	12.6	860
P235/75R15XL	108T	OWL	560A	6.5	227	732	1002	10.7	12.6	850
P175/70R13	82T	WW	560A	5.0	177	576	476	9.5	6.8	1700
P175/70R13	82T	BW	480A	5.0	168	572	476	10.0	6.8	1700
P185/70R14	87T	BW	560A	5.5	182	613	546	10.2	7.8	1600
P195/70R14	90T	BW	560A	6.0	194	628	601	10.2	8.8	1350
P205/70R14	93T	WW	560A	6.0	200	640	651	10.2	9.9	1300
P215/70R14	96T	WW	560A	6.5	208	656	711	11.0	10.0	1080
P205/70R15	95T	WW	560A	6.0	199	665	691	10.6	9.7	1250
P215/70R15	97T	WW	560A	6.5	211	681	731	10.7	10.8	1150
P225/70R15	100T	WW	560A	6.5	216	694	802	10.7	11.6	950
P175/65R14	81T	BW	560A	5.0	165	582	463	10.2	7.0	1700
P185/65R14	85T	BW	560A	5.5	179	595	516	10.0	7.7	1590
P195/65R14	88T	BW	560A	6.0	191	605	561	10.2	8.7	1350
P185/65R15	86T	BW	560A	5.5	179	616	531	10.0	8.0	1520
P195/65R15	89T	BW	560A	6.0	192	632	561	10.2	9.0	1310
P205/65R15	92T	BW	560A	5.5	199	643	581	10.7	9.7	1255
P215/60R16	94T	BW	480A	6.5	208	661	671	10.7	11.0	1000
P225/60R16	97T	BW	480A	6.5	213	673	691	11.3	11.0	950



41 Ardelt Place  
 Kitchener, Ontario, CANADA N2C 2C8  
[www.herculestire.com](http://www.herculestire.com)