

# METRIC SE-T



- All season design with a tread design that reduces road noise and increases all weather traction.
- T-Speed rated to meet the demands of today's import cars.

**UTQG**  
400AA

item code	tire size	side wall	service desc.	tire weight	rim width	tread depth	max load	max psi	section width (infl)	overall diam (infl)
19134	145/80R13	BLK	75T	12.8	4.00	9.5	853	35	5.71	22.1
19135	155/80R12	BLK	77T	13.0	4.50	9.5	915	35	6.18	21.8
19132	155/80R13	BLK	79T	13.9	4.50	9.5	959	35	6.18	22.8
19133	165/80R13	BLK	83T	15.8	4.50	9.5	1069	35	6.50	23.4

PERFORMANCE TIRE



# SIGNET DH II 60/65

- Engineered for superior traction on both wet and dry roads.
- Increased siping for added wet weather confidence.
- Integrated balanced design improves steering response, cornering, and even wear.

**UTQG**  
400AA

item code	tire size	side wall	service desc.	tire weight	rim width	tread depth	max load	max psi	section width (infl)	overall diam (infl)
45028	175/60R13	BLK	77 H	15.0	5.00	11.0	908	44	6.85	21.34
45029	185/60R13	BLK	80 H	16.0	5.50	11.0	992	44	7.36	21.77
45030	185/60R14	BLK	82 H	17.0	5.50	11.0	1120	44	7.36	22.76
45031	195/60R14	BLK	86 H	18.0	6.00	11.0	1168	44	7.83	23.23
45032	205/60R14	BLK	88 H	21.0	6.00	11.0	1235	44	8.15	23.62
45033	215/60R14	BLK	91 H	22.0	6.50	11.0	1356	44	8.62	24.09
45034	195/60R15	BLK	88 H	19.0	6.00	11.0	1235	44	7.83	24.13
45035	205/60R15	BLK	91 H	22.0	6.00	11.0	1365	44	8.11	24.68
45036	215/60R15	BLK	94 H	23.0	6.50	11.0	1477	44	8.62	25.08
45037	225/60R15	BLK	96 H	24.0	6.50	11.0	1565	44	8.90	25.55
45075	215/60R16	BLK	96 H	25.0	6.50	10.5	1477	35	8.74	25.96
45077	225/60R16	BLK	96 H	27.0	6.50	10.5	1609	35	9.14	26.40
45038	175/65R14	BLK	82 H	17.0	5.00	11.0	1047	44	6.93	23.03
45039	185/65R14	BLK	86 H	17.0	5.50	11.0	1168	44	7.48	23.54
45040	195/65R14	BLK	89 H	19.0	6.00	11.0	1279	44	7.80	24.13
45041	185/65R15	BLK	88 H	18.0	5.50	11.0	1235	44	7.40	24.49
45043	195/65R15	BLK	91 H	20.0	6.00	11.0	1356	44	7.87	25.04
45044	205/65R15	BLK	94 H	23.0	6.00	11.0	1477	44	8.07	25.67
45046	215/65R15	BLK	96 H	24.0	6.50	11.0	1565	44	8.66	26.06