



TOURING SE

- SR-Speed rated for handling/performance.
- Power sweep tread design for all-season performance.
- Elegant touring tire appearance.
- Deep grooves resist hydroplaning.
- Advance tread compound provides long life.

UTQG

70-65-60-55: 560AB

PASSENGER TIRE

item code	tire size	side wall	service desc.	tire weight	rim width	tread depth	max load	max psi	section width (infl)	overall diam (infl)
03471	P205/70SR14	.65"	93 S	20.0	6.00	11.0	1433	35	8.1	25.3
03472	P215/70SR14	.65"	96 S	22.0	6.50	11.0	1554	35	8.6	25.8
03473	P205/70SR15	.75"	95 S	21.0	6.00	11.0	1499	35	8.1	26.3
03475	P215/70SR15	.75"	97 S	22.0	6.50	11.0	1620	35	8.6	26.8
03486	P205/55SR16	BLK	89 S	22.0	6.50	10.5	1279	35	8.3	24.8
03484	P215/60SR16	BLK	94 S	23.0	6.50	11.0	1477	35	8.6	26.1
03485	P225/60SR16	BLK	97 S	24.0	6.50	11.0	1609	35	8.8	26.5
03477	P175/65SR14	BLK	81 S	16.0	6.85	10.5	1019	35	6.9	23.0
03478	P185/65SR14	BLK	85 S	17.0	5.50	10.5	1124	35	7.4	23.4
03479	P195/65SR14	BLK	88 S	19.0	6.00	10.5	1235	35	7.8	24.0
03480	P195/65SR15	BLK	89 S	19.0	6.00	10.5	1279	35	7.8	24.9
03482	P205/65SR15	BLK	92 S	21.0	6.00	11.0	1400	35	8.2	25.4
03483	P215/65SR15	BLK	95 S	22.0	6.50	11.0	1510	35	8.7	26.0
03460	P175/70SR13	BLK	82 S	14.0	5.00	10.5	1036	35	6.9	22.7
03462	P185/70SR13	BLK	85 S	16.0	5.50	10.5	1135	35	7.4	23.2
03465	P175/70SR14	BLK	84 S	16.0	5.00	10.5	1102	35	6.9	23.7
03467	P185/70SR14	BLK	87 S	17.0	5.50	10.5	1201	35	7.4	24.2
03469	P195/70SR14	BLK	90 S	18.0	6.00	10.5	1312	35	7.8	24.8
03474	P205/70SR15	BLK	95 S	20.0	6.00	11.0	1499	35	8.1	26.3

